



CaviBlaster 0625-G

Gasoline Engine with Electric Start, 6 gpm & 2,500 psi

Specifications and Options

Designed as a dependable & durable, yet lightweight and flexible solution for the low budget cleaning operations, the 0625-G has proven to be a great first step into cavitation

Accessories Included:

Unbalanced diver gun, high pressure hose(50 feet), battery start, electric suction pump, Feed Hose/Pump, Pressure washer gun/wand assembly, 4 color coated pressure washing tips



Optional Accessories:

Additional pressure hose available in 50 ft or 100 ft sections
Maximum Pressure hose length up to 300 ft (100 meters) total

SKID Dimensions	
Length w/o handle	27" / 69 cm
Length w handle	33" / 84 cm
Width wheel base	22" / 56 cm
Height	21" / 53 cm
Weight	165 Lbs / 75 Kg

Pump System	
Pressure Pump	AR RKV55G40
Pump Material / Type	Brass / Positive Displacement
Flow Rate	5.5 gpm / 21 Lpm
Nozzle Pressure	2,500 psi / 172 Bar
Hose Diam/Max Lgth	3/8" – 50 ft / 100 m

Shipping Dimensions	
Pallet 40x48x36"	260 Lbs Gross weight

Drive System	
Engine	CH440
Engine Type	4-Stroke OHV
Cooling System	Air
Ignition System	Digital CDI, Variable Timing
Max Output HP/kW	14 HP / 10,5 kW
Clutch	Direct Drive
Starting System	Electric

Feed System	
Feed Pump	Johnson L1600
Pump Material	Thermoplastic, SS Shaft
Flow Rate @ Max Lift	23gpm/88L/m @ 3.3Lft/1m
Pump Power supply	12 V @ 7 Amp

Ideal For
Small to Mid size Boat Hulls
Piers, Pilings & Seawalls
Running gear & Out drivers
Pools & Indoor Underwater Instalations



Tool
Unbalanced Gun

* Pricing and specifications subject to change without notice

CaviDyne LLC, 5077 Fruitville Rd. Suite - 109-157, Sarasota FL, 34232 USA

Phone: (352)275-5319, sales@cavidyne.com, www.cavidyne.com