

CaviBlaster 2022-D

Diesel Engine, 20 gpm & 2,200 psi

Specifications and Options

This is our largest commercial unit, operating at lower pressures it's designed specifically not to damage paints or coatings yet strong enough to clean to bare metal if needed



Feed Hose (15 feet), By-Pass Hose (15 feet), High Pressure Hose (50 feet), Zero-Thrust Balanced Gun, Battery Start

Optional Accessories:

Aditional pressure hose available in 50 ft or 100 ft sections

Max. Pressure hose length recommended up to 300 ft (100 meters) total



Pump System		
Pressure Pump	Udor NX 75/150	
Pump Material / Type	Brass / Triplex	
Flow Rate	20 gpm / 76 Lpm	
Nozzle Pressure	2,200 psi / 152 Bar	
Hose Diam/Max Lgth	3/4"-600ft@19mm/180m	

Shipping Dimensions	
Pallet 40x48x48"	1,000 Lbs Gross weight

Drive System		
Engine	Kubota D1105-T-E3B	
EPA Regulation	USATier-4 / EUStage III-A	
Engine Type	4 Cyl / 4-Cycle	
Cooling System	Liquid w/Axial fan	
Combustion System	Turbo Charged	
Exhaust	CycloneMfr / Spk arrester	
Int. Output	32.8 HP / 24.5 kW	
Transmission	Centrifugal clutch	
Starting System	Electric Starter	
Emergency Shut-off	YES	



Feed System	
Feed Pump	Centrifugal Self-Priming
Pump Material	Marine Bronze /SS Shaft
Flow Rate / Height	125 GPM/475 I/m @6Ft/2m
Drive	Belt Driven



Tool Options	
Zero-Thrust Balanced Gun	
Single CaviDome	
ROV Lance	



^{*} Pricing and specifications subject to change without notice