

CaviBlaster 2570-D

Diesel Engine, 29 gpm & 7,250 psi

Specifications and Options

This is an industrial workhorse which generates a super stream of high velocity cavitation for high efficient cleaning, it can strip fouling and corrosion to bare metal if desired


This unit is capable of achieving surface preparation stage Sa.2.5



Feed Hose (15 feet), By-Pass Hose (15 feet), High Pressure Hose (50 feet), Zero-Thrust Balanced Gun, Battery Start


Optional Accessories:

Aditional pressure hose available in 50 ft or 100 ft sections. (3/4" Diam.) Max. Pressure hose length recommended up to 300 ft (100 meters) total




Pump System		
Pressure Pump	HPP H-150/3 SAP	
Туре	Positive Displacement	
Flow Rate	29 GPM / 110 L/min	
Nozzle Pressure	7,200 psi / 500 Bar	
Hose Diam/Max.Length	3/4" / 600 Lft - 19 mm / 200 m	

Shipping Dimensions	
Pallet 58x98x70"	6,000 Lbs Gross weight



	Feed System		
l	Feed Pump	Centrifugal Self-Pr	
l	Flow Rate	80 GPM/304 L/mir	
1	Lift	20Ft / 6 m	
l	Power transm.	Belt	
1			
l			
1			

Tool Options	
ZT Balanced Dump-Gun	





^{*} Pricing and specifications subject to change without notice